

ZKP8005

Thermal Receipt Printer



ZKP8005 is a high-performance thermal receipt printer with auto-cutter. This thermal receipt printer has good printing quality, high printing speed and good stability, which is widely used in POS system, catering industry and different sectors.

Features

- Hidden cable slot, specially designed for wall mounting
- Lightweight and compact design
- High-quality printing in low cost
- Low noise and high-speed printing
- Suitable for all types of commercial retail POS systems, Restaurant systems, Industrial control systems

Applications



Retail Industry



Supermarkets



Fashion Chain Stores



Pharmacy

Specifications

Print Method	Direct thermal
Paper Width	79.5±0.5mm
Print Speed	230 mm/s
Print Width	72mm
Character Set	Alphanumeric; International
Character Size	ANK Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
Print Resolution	576 dots/line or 512 dots/line (Adjusted by command)
Line Spacing	3.75mm (Adjusted by command)
Column Number	Font A: 42 columns or 48 columns
Extension Character Sheet	PC437(standard Europe) (Katakana) PC850(Multilingual) PC860(Portugal) PC863(Canadian) PC865(Nordic) (West Europe) (Greek) (Hebrew) (East Europe) (Iran) (WPC1252) PC866(Cyrillic#2) PC852(Latin2) (PC858) (Iran II) (Latvian) (Arabic) (PT1511251)
1D Barcode Types	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128
Auto Cutter	Partial
Interface	USB+LAN
Print Command	ESC/POS
Power Adapter	Input: AC 100-240V/50-60 Hz Output: DC24V/2.5A
Printer Input	DC 24V/2.5A
Cash Drawer	DC 24V/1A
Cutter Life	1.5 million cuts
Printer Head Life	100KM
Dimensions (D*W*H)	192*145*133 (mm)
Net Weight	1.00 Kg
Weight with Packaging	2 Kg
Operating Temperature	0°C to 45°C
Storage Temperature	-10°C to 60°C
Operating Humidity	10% to 80%RH
Storage Humidity	10% to 90%RH
Certificates	CE; FCC; RoHS

