



System Features

OS	Android 11
GMS certified	GMS certified
CPU	Octa-core 2GHz Processor
Memory	4 GB RAM / 64 GB Flash
Languages support	Multiple languages
Others	Input Chinese/ English Supports handwriting and soft keyboard

Display

Screen Size	5.0" TFT-LCD HD (720 x 1280) color screen
Touchpanel	Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance

Keypad

Side SCAN button x 2 (Left / Right), User-defined function button (programmable key), volume up/down buttons, on/off button

Camera

8MP front camera
13M rear camera with LED flash and auto-focus function

Indicator Type

LED, Speaker, Vibrator

Symbologies

Support all major 1D and 2D barcodes

RFID

HF Support HF/NFC, Frequency 13.56Mhz, ISO14443 A/B, ISO15693, Felica(ISO/IEC18092), Mifare compliance

Power Source

Main Battery 3.85V 4250mAh Li-ion battery
Removable

Software

SOTI, AirWatch, 42Gears, and MoboLink

Regulatory Approvals

CE, FCC, NCC, CCC, SRRC, VCCI, TELEC, RoHS, BQB, N-Mark, BSMI for battery

Communication

Bluetooth®	Bluetooth® 5 supported
WLAN	802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v, 2.4G+5GHz, support fast roaming, VoWiFi, hotspot, Compliant with WFA, WPA/WPA2
WWAN	Global: 4G LTE FDD: B1/B2/B3/B5/B7/B8/B20/B28A/B28B TDD: B38/B39/B40/B41 3G WCDMA: B1/B5/B8 2G GSM: 850,900,1800,1900MHz Americas : 4G LTE FDD-B1/B2/B4/B5/B7/B12/B13/B14/B17/B28A/B28B TDD-B38/B40/B41 3G WCDMA: B1/2/4/5/8 2G GSM: 850,900,1800,1900MHz
GPS	AGPS, GPS, GLONASS, Beidou, Galileo
Sensors	Light Proximity, Accelerometer, e-Compass, Gyroscope sensor
Fingerprint	Optional

I/O Interfaces

USB	USB 2.0 (Type-C)
OTG	Yes, over USB Type-C
POGO PIN	Charging via cradle
SIM Slot	Dual SIM , support LTE + LTE
Expansion Slot	MicroSD, up to 256 GB
Audio	One speaker (1.5W / 95±3dB @ 10cm), One receiver, Dual noise-cancelling microphones

Enclosure

Dimensions	151.1mm x 76.8mm x 13.7mm
Weight	246g (with battery)

Environmental

Operating temperature	-20°C to 60°C
Storage temperature	- 40°C to 70°C (without battery)
Charging temperature	0°C to 45°C
Relative Humidity	95% (non-condensing)
Drop Specification	1.5m , 1.8m with boot case
Sealing	IP67
Vibration/ Tumble test	0.5m tumbles for 300 cycles / 600 drops

Accessories

- USB 2.0 type C cable
- 5V/2A Adaptor
- PE+ Adaptor
- Single Slot Charging Cradle
- Single Slot USB Cradle
- 4-Slot Terminal Charging Cradle
- 4-Slot Battery Charger
- Gun grip
- Glass Screen Protector
- Protective Case
- Hand Strap
- Wearable Kit w/ bracket, strap, pad
- Vehicle Cradle



Headquarters

Taipei, Taiwan
http://www.ute.com e-mail: info@hq.ute.com

unitech America

Los Angeles
http://us.ute.com e-mail: info@us.ute.com
http://can.ute.com info@can.ute.com

Mexico
http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
http://apac.ute.com info@apac.ute.com / info@india.ute.com
http://mideast.ute.com info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

Tokyo
http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
http://cn.ute.com info@cn.ute.com
Taipei http://tw.ute.com info@tw.ute.com

