

SC01TD-W0605

Smart POS Terminal



ZKTeco introduces the **SC01TD-W0605**, a comprehensive point-of-sale system. This series includes three models, each with a dual display and an all-in-one design. The modular design also consists of an MSR reader (optional) and an RFID reader (optional) for convenient payment and improved retail experience. Moreover, the SC01TD-W0605 has a fanless system with an innovative heat pipe design that supports long operating hours.

Features

- All-in-one POS with 15.6" True-Flat PCAP Touch Screen, HD & FHD LCD Screen
- Modular Design and Optionally Embedded with MSR & RFID Reader for Convenient Payment
- Hidden Cable Management for Sleek Design
- Fanless System with Innovative Heat Pipe Design to Avoid the Spread of Grease and Heat within the POS Terminal

Applications



Retail Outlets



Restaurants



Cafes



Coffee Shops



More

Specifications

| | |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model | SC01TD-W0605 |
| CPU | Intel® Core® i5-4120U @ 2.30GHz |
| Memory | 8GB RAM, DDR3 128GB SSD |
| Display | Configuration 1: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive Touch Screen; Second: LED (8C digital tube) Configuration 2: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive Touch Screen; Second: VFD (2*20 lines) Configuration 3: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive Touch Screen; Second: 11.6" HD, 1366*768 |
| Material | ABS plastic |
| Colour | Black and Gray, White (Optional) |
| Operating System | Supported Windows System 7, 8, 10, 11 |
| Dimension | 345*180*354mm |
| Packing Dimension | 385*240*415mm |
| Net Weight | Configuration 1&2: 4.7Kg Configuration 3: 5.6Kg |
| Gross Weight | Configuration 1&2: 5Kg Configuration 3: 5.9Kg |
| Interface (s) | 4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port |
| Power Supply | DC12V/5A |
| Wi-Fi (Optional) | IEEE 802.11 a/b/g/n/ 2.4GHz (Single-band) IEEE 802.11 a/b/g/n/ 2.4GHz /5GHz (Dual-band) |
| Bluetooth | Not Support |
| Speaker | 2*2W (Optional) |
| Peripherals (Optional) | Built-in MSR reader Built-in RFID reader |
| Operating Humidity | 20% to 80% RH (Non-condensing) |
| Storage Humidity | 20% to 80% RH (Non-condensing) |
| Operating Temperature | 0°C to 40°C |
| Storage Temperature | -15°C to 60°C |
| Certification (s) | ISO9001, CE, FCC, RoHS |

